



DOMINATOR™ HIRO®

KEY FEATURES & INCLUDES:

Opener with LED light
1400N Short-term peak force
Soft Start / Soft Close
Intelligent Safety System
Smart phone compatible
(1) Wireless wall button
(2) Remote controls
Wired Safety Beams
DBCI sheet door adapters

OPTIONAL ACCESSORIES:

Wireless Keypad



automatic
TECHNOLOGY

Compatible with doors over 14'
in Series **1950**, **1950HD**, **2000**, **2500**,
and all sizes of the **3100** Series
up to maximum sq footage.

COMMERCIAL DOOR OPENER

Discover how DBCI can provide the service, performance and reliability your project demands.

800-542-0501
dbci.com

WARRANTY

- 2 year/10,000 cycles on parts
- 1 year on accessories



The **HIRO** delivers you both control and connectivity via the in-built smartphone control system. Whether you have a very large roller door, a wind-locked door, or require low side room compatibility, the Hiro opener is the perfect choice for your commercial and industrial needs.

DBCI is a leading manufacturer of commercial-grade steel doors, components, and accessories.

TECHNICAL SPECIFICATIONS

Power	Input Voltage	120V a.c. / 60 Hz
	Motor Type	24V d.c. Permanent Magnet
	Current (max)	2A
	Short-Term Lifting Force	400N
Installation**	Door Size	300 ft ²
	Door Size (wind-lock)	236 ft ²
Transmitter System	Receiver/Transmitter Frequency	Multi-frequency UHF FM (434.37, 433.47 & 433.92MHz)
	Coding System	TrioCode™ 128, code hopping
	Code Combinations	3.4x10 ³⁸ code combinations
	Transmitter Type	TrioCode™ 128
	Transmitter Capacity (x 4-button registers)	64
Additional Features	Courtesy Light	LED
	Safety Beam Compatibility	2-wire Safety Beams
	Installation	Suits most sheet doors*
	Battery backup	Optional
Warranty*	2 year/10,000 cycles on parts 1 year on accessories	

*Please see full warranty terms and conditions on our website. This brochure is not evidence of our warranty. Our warranty is in addition to any consumer guarantees that may apply under American Law.

**Suitable for use on dead axle doors. Windy conditions can activate the obstruction feature of the opener.

